

Trade Name:	STAHL Chemical Anchor M 8 – M 16
Producer/Supplier:	Stahl GmbH
Printing Date:	28.06.2001

1. Identification of the substance/preparation and of the company/undertaking**1.1 Description of substance or preparation**

STAHL Chemical Anchor M 8 A- und B- Compound
STAHL Chemical Anchor M 10 A- und B- Compound
STAHL Chemical Anchor M 12 A- und B- Compound
STAHL Chemical Anchor M 14 A- und B- Compound
STAHL Chemical Anchor M 16 A- und B- Compound

1.2 Firm Name

Stahl GmbH, Gerberstr. 18, D - 73650 Winterbach
Telephone 07181/97772-0 Telefax 07181/97772-22

1.3 Telephone in case of emergencies/Office for advice

Alternative contact within the North America:
Wej-it Fastening Systems, 2415 E. 13th Place, Tulsa, OK 74104
Telephone (918) 744-7444 Fax (918) 744-9918

1.3.1 Telephone number of the firm in case of emergencies:

Tel.: 07181/97772-0
Or Wej-it Fastening Systems Telephone (918) 744-7444 Fax (918) 744-9918

2. Composition/information on ingredients**2.1 Chem. name / % content / symbol / R-phrases**

Dibenzoyl peroxide; 30 - 60; E/Xi; 2-7-36-43; CAS 94-36-0
Styrene; 1 < 12,5; Xi/Xn; 10-20-36/38; CAS 100-42-5

3. Hazards identification**3.1 To people**

Product is flammable
Skin contact:
May cause sensitization by skin contact.
Product is oxidizing.
Eye contact:
Irritation of the eyes
These details refer to the cartridge before usage.

3.2 To the environment

See point 12.
Toxicity to fish:
LC50 *Leuciscus idus* 35 mg/l/48h (Styrene)
LC50/96h 2 mg/L *Poecilia reticulata* (Dibenzoyl peroxide); NOEC/96h 0,7 mg/l
Toxicity to daphnia:
LC50/96h 3,7 mg/l *Daphnia magna* (Dibenzoyl peroxide)
Toxicity to bacteria:
EC10 *Pseudomonas putida* 250 ul/l/18h (Styrene)

Trade Name:	STAHL Chemical Anchor M 8 – M 16
Producer/Supplier:	Stahl GmbH
Printing Date:	28.06.2001

4. First aid measures

4.1 Inhalation

Remove person from danger area.
Supply person with fresh air.
Keep data sheet available.

4.2 Eye contact

Wash thoroughly for several minutes using ample water
(eye-wash bottle if possible) - call doctor immediately.
Have data sheet available.

4.3 Skin contact

Wash thoroughly with soap and water - consult doctor if necessary.
Remove contaminated clothing immediately.

4.4 Ingestion

Call doctor immediately, have data sheet available.
Delayed effects from exposure can be expected (Styrene).

4.5 Special resources necessary for first aid

n.c.

5. Fire-fighting measures

CO₂
Water jet spray
Dry extinguisher

5.2 Unsuitable fire extinguisher for reasons of safety

Water jet

5.3 Special dangers caused by the substance of preparation itself, results of fire/burning, or ensuring gases

In case of fire the following can develop:

Gases hazardous to health
Carboxylic acids
Oxides of carbon
Organic decomposition products
Flammable vapour/air mixtures
Vapours hazardous to health

5.4 Special protective equipment for fire fighting

Protective respirator with independent air supply.
According to size of fire
Full protection, if necessary

6. Accidental release measures

6.1 Personal precautions

Remove possible causes of ignition - do not smoke.
Avoid contact with eyes or skin.
Caution - possibility of sliding.

Trade Name:	STAHL Chemical Anchor M 8 – M 16
Producer/Supplier:	Stahl GmbH
Printing Date:	28.06.2001

6.2 Environmental measures

Prevent from entering drainage system.
If leakage occurs, dam up.

6.3 Procedure for cleaning up

Collect using absorbant material (e.g. Universal binding medium), and dispose according to point 13. Collect mechanically and dispose according to point 13.

7. Handling and storage**7.1 Handling****Tips for safe handling:**

Only use working methods according to operating instructions.
Keep away from sources of ignition - do not smoke.
General hygiene measures for the handling of chemicals are applicable.

7.2 Storage

Not to be stored in gangways or stair wells.
Only store products unopened, in original packing.
Observe TRGS 515.

Special storage conditions:

See point 10.2
Store cool
Do not store over 25° C.
Protect against moisture and store closed.
Danger of explosion by storing in sealed containers.

8. Exposure controls/personal protection**Chem. name / % content / MAK-value / TRK-value / BAT-value / CAS**

Dibenzoyl peroxide; 30 - 60; MAK 5 mg/m³ / = 1
Styrene; 1 - 12,5; MAK 20 ppm (86 mg/m³); BAT 600 mg/g

- | | | |
|-----|------------------------------------|---|
| 8.1 | Respiration protection: | If MAK-value is exceeded. A or A-P2 |
| 8.2 | Hand protection: | Protective PVC gloves |
| 8.3 | Eye protection,
face protection | Tightly fitting protective goggles with side protection |
| 8.4 | Body protection: | Protective working garments |

9. Physical and chemical properties

Physical state:	B: solid, powder A: liquid
Colour:	B: white A: yellow
Odour:	B: odourless A: characteristic
pH-value undiluted:	B: 7
Boiling point/range (in ° C):	B: decomposition > 60 (SADT) A: 145 (Styrene)

Trade Name:	STAHL Chemical Anchor M 8 - M 16
Producer/Supplier:	Stahl GmbH
Printing Date:	28.06.2001

Melting point/range (in ° C) :	B: ≈ 55 A: -31 (Styrene)
Flash point in ° C:	A: 31 (Styrene)
Autoflammability:	B: No
Oxidizing properties:	B: Yes A: No
Minimum limit of explosion:	A: 1,1 Vol% (Styrene)
Maximum limit of explosion:	A: 8,9 Vol% (Styrene)
Vapour pressure:	A: 6 hPa/20° C (Styrene)
Relative density (g/cm ³):	A: 1,15/20° C
Bulk density (kg/m ³):	A: 630/20° C
Solubility in water:	A/B: Insoluble
Viscosity:	A: 2200 mPas/23° C
A = Resin compound B = Peroxide compound	

10. Stability and reactivity

10.1 Conditions to avoid

see point 7.

Heating > 60° C- exothermic decomposition/polymerisation.

Protect from humidity.

Heating, open flame, ignition sources.

10.2 Materials to avoid

see point 7.

Avoid contact with other chemicals.

Rust, bases, amines, acids - violent reaction.

Heavy metal salts.

Avoid contact with strong alkalis.

Avoid contact with oxidizing agents.

10.3 Hazardous decomposition products

See point 5.3

10.4 Additional information

Stabilizers necessary: Yes

Stabilizers available: Yes

Effects of changes in physical state, on safety: Yes

11. Toxicological information

11.1 Acute toxicity

11.1.1 Ingestion, LD50 rat oral (mg/kg): n.d.a.

11.1.2 Inhalation, LC50 rat inhaling (mg/l/4h): n.d.a.

11.1.3 Skin contact, LD50 rat dermal (mg/kg): n.d.a.

11.1.4 Eye contact: B: Irritant

11.2 Chronic effects

11.2.1 Sensitization: B: Yes (skin contact)

11.2.2 Carcinogenicity: n.d.a.

11.2.3 Mutagenicity: n.d.a.

Trade Name:	STAHL Chemical Anchor M 8 - M 16
Producer/Supplier:	Stahl GmbH
Printing Date:	28.06.2001

11.2.4 Reproductive toxicity: n.d.a.

11.2.5 Narcosis: n.d.a.

11.3 Further information

Classification according to calculation method.

12. Ecological information

12.1 Water hazard class: B: 1 A: 2

12.2 Self classification: Yes (VwVwS)

12.3 Degrability: CE50/30 Min. 35 mg/l
(degradability of activated sludge
Dibenzoyl peroxide)

12.4 Behaviour in sewage plants: n.d.a.

12.5 Aquatic toxicity: see point 3

12.6 Ecological toxicity: see point 3.

13. Disposal considerations

13.1. for the material/preparation/residue

EC disposal code number: 08 04 04 (hardened adhesives and sealants)

Recommendation:

Pay attention to local and national official regulations.

E.g. dispose at suitable refuse site.

13.2 For contaminated packing material

See point 13.1

Pay attention to local and national official regulations.

14. Transport information

General statements

UN-Number: 3269

Road/Rail-transport (GGVS/ADR/GGVE/RID)

GGVS/ADR: 3/31c (class/number)

3269 Polyester resin kit

Transport by sea

GGVSee/IMDG-Code: 3.3/3377-1/III (class/code/packing group)

EmS-Number: 3-07

MFAG-Number: 310

Marine Pollutant: Yes

Polyester resin kit (Styrene monomer, inhibited)

Transport by air

IATA: 3/-/III (class/code/packing group)

Polyester resin kit

Additional information:

Minimum amount regulations have not been taken into account.

Danger code and packing code on request.

Trade Name:	STAHL Chemical Anchor M 8 – M 16
Producer/Supplier:	Stahl GmbH
Printing Date:	28.06.2001

15. Regulatory information**Classification according to Dangerous Product Regulations incl.****EEC Guidelines****(67/548/EEC and 88/379/EEC)**

Symbol: B: Xi/O A: --

Description of danger:

Compound B:

Irritant

Oxidizing

Compound A:

--

R-phrases:

Compound B:

7 May cause fire.

36 Irritating to eyes.

43 May cause sensitization by skin contact.

Compound A:

10 Flammable.

S-phrases:

Compound B:

(2) Keep out of the reach of children.

3/7 Keep container tightly closed in a cool place.

14 Keep away from dirt, rust, alcalis, acids and accelerators (like heavy metal salts and amines).

36/37/39 Wear suitable protective clothing, gloves and eye/face protection

(46) If swallowed, seek medical advice immediately and show this container or label.

Compound A:

(2) Keep out of the reach of children.

(46) If swallowed, seek medical advice immediately and show this container or label.

Additions:

B: Dibenzoyl peroxide A: --

VbF:

n.a.

Observe restrictions:

Yes

16. Other details

These details refer to the product as it is delivered.

Storage class VCI: 5.2

Revised points: 1 - 16

Trade Name:	STAHL Chemical Anchor M 8 – M 16
Producer/Supplier:	Stahl GmbH
Printing Date:	28.06.2001

Legend:

n.a. = not applicable / n.c. = not checked / n.d.a. = no data available

VbF = regulations for flammable liquids / MAK = maximum concentration per work place in ml/m³ = ppm

BAT = biological tolerance for work places / TRbF = technical regulations for flammable liquids

WGK = water hazard class

WGK3 = very hazardous to water WGK2 = hazardous to water

WGK1 = slightly hazardous to water WGKO = generally not hazardous to water

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics, but they are based on our present up-to-date knowledge. No responsibility.